

Öffentliche Netze

Voice over IP

Als Basis für die Konfiguration kann die Datei `/etc/sipwitch.conf` (Basiskonfiguration) und für die Anlage der Benutzer `/etc/sipwitch.d/lab.xml-sample`

[.sipwitchrc_sample](#)

```
<?xml version="1.0"?>
<sipwitch>
  <!-- master config file. The default config can be overridden with
a
  runtime one stored in /var/run/sipwitch which can be installed by
  a management system. If one is using a server executed under "user"
  permissions, then this would be ~/.sipwitchrc.
  Erklärung:
  http://www.gnutelephony.org/index.php/GNU_SIP_Witch_configuration

  Konfig: .sipwitchrc in Home-Ordner kopieren.
  Aufruf: sipw -x9 -f
  -->
  <provision>
<!-- Allows provisioning to be in main config file as well as
scattered.
  This allows one to produce a single config file that represents
the
  complete phone system.

  <refer id="x"></refer>
  <alias id="test"><contact>sip:xxx@yyy</contact></alias>
  <user id="y"/>
  <gateway id="z"/>
  -->
  <test id="testing">
    <secret>editme</secret>
    <extension>299</extension>
    <answer>12</answer>
    <duration>120</duration>
    <display>Testing</display>
  </test>

  <user id="editme1">
    <secret>editme</secret>
    <extension>201</extension>
    <display>editme 1</display>
  </user>

  <user id="editme2">
```

```
<secret>1234</secret>
<extension>202</extension>
<display>editme 2</display>
</user>

</provision>

<access>
  <!-- Access rules and cidr definitions. By default 127.0.0.1/::1
are in
  a pre-generated "loopback" cidr. Access rule entries are now
  automatically generated by scanning the network interface, so this
  is for special overrides or convenience naming.
<local>172.16.59.0/24</local>

<local>0.0.0.0/01</local>
<local>128.0.0.0/01</local>
-->
  <local>editme</local>
</access>

<stack>
  <!-- The effective names this server processes requests for, and an
optional
  list of host or domain names this server will also respond to.
The
  default hostname is always accepted.
  <localnames>sip.gnutelephony.org, server.local, something
somewhere</localnames>
-->

<!-- Stack configuration. Here we restrict all access to the server
under
  the local subnet, and we specify the local subnet is "trusted".
Trusted
  means that challenge digests will be relaxed for devices that are
  already registered with the server, and hence reduces the total
sip
  traffic needed. We map for 200 calls, set 2 dispatch threads for
  sip events, and bind to all interfaces.
  <restricted>local</restricted>
  <trusted>local</trusted>

-->

<mapped>200</mapped>
<threading>2</threading>
<interface>*</interface>
<dumping>>false</dumping>

<!-- peering entry used for setting "proxy" ip address for external
```

```

users
  when we are behind a NAT. This is used for determining ip address
  for
  media proxy in particular. Example entry shown. Can be ip address
  or
  resolvable hostname.

  <peering>www.example.com</peering>
-->

<!-- special user id's. The "system" id is used when the server
creates a
  sip message that is not on behalf of any registered "ua", but
  rather
  from the server itself. For example, when feeding a sms "message"
  through the control interface, this is generated as a "system"
message.
  Attempts to dial the "system" id will always return SIP FORBIDDEN.

  The "anon" id is used when anonymous messages are generated. These
  always respond with SIP NOT FOUND if one wishes to contact anon.
-->
  <system>
    system
  </system>
  <anon>
    anonymous
  </anon>
</stack>

<timers>
  <!-- ring every 4 seconds -->
  <ring>4</ring>
  <!-- call forward no answer after x rings -->
  <cfna>4</cfna>
  <!-- call reset to clear cid in stack, 6 seconds -->
  <reset>6</reset>
</timers>

<!-- we have 2xx numbers plus space for external users -->
<registry>
  <prefix>200</prefix>
  <range>100</range>
  <keysize>77</keysize>
  <mapped>200</mapped>

  <!-- ACHTUNG: Der Tag <realm> muss mind. einen "." enthalten und
  darf keine
  Leerzeichen beinhalten.!
  s. Hier:
  http://lists.gnu.org/archive/html/sipwitch-devel/2011-01/msg00007.html

```

```
-->  
  <realm>editme</realm>  
</registry>  
  
<routing>  
  
</routing>  
</sipwitch>
```

From:
<https://www.kopfload.de/> - **kopfload - Lad Dein Hirn auf!**

Permanent link:
<https://www.kopfload.de/doku.php?id=network:lf9&rev=1349107800>

Last update: **2025/11/19 16:12**

